

## TI-5104 lithium battery

5 ; Tadiran Lithium Thionyl Chloride Batteries are designed to provide high performance power in less space. These lithium thionyl chloride (Li/SOCl<sub>2</sub>) cells feature greater energy density, up to 710Wh/Kg and 1420Wh/I. Tadiran Li/SOCl<sub>2</sub> have an open circuit voltage of 3.67V, an operating voltage of up to 3.6V, and -55°C to +125°C ...

Tadiran Lithium Thionyl Chloride Batteries are designed to provide high performance power in less space. These lithium thionyl chloride (Li/SOCl<sub>2</sub>) cells feature greater energy density, up to 710Wh/Kg and 1420Wh/I. Tadiran Li/SOCl<sub>2</sub> have an open circuit voltage of 3.67V, an operating voltage of up to 3.6V, and -55°C to +125°C operating ...

3 ; Tadiran Lithium Thionyl Chloride Batteries are designed to provide high performance power in less space. These lithium thionyl chloride (Li/SOCl<sub>2</sub>) cells feature greater energy density, up to 710Wh/Kg and 1420Wh/I. Tadiran Li/SOCl<sub>2</sub> have an open circuit voltage of 3.67V, an operating voltage of up to 3.6V, and -55°C to +125°C ...

6 ; Tadiran Lithium Thionyl Chloride Batteries are designed to provide high performance power in less space. These lithium thionyl chloride (Li/SOCl<sub>2</sub>) cells feature greater energy density, up to 710Wh/Kg and 1420Wh/I. Tadiran Li/SOCl<sub>2</sub> have an open circuit voltage of 3.67V, an operating voltage of up to 3.6V, and -55°C to +125°C ...

The TL-5104/S-BP is an AA 3.6V/2.1Ah Non-rechargeable Battery features a lithium technology, raised positive and flat negative terminals. This lithium battery has standard terminals. Typical values at 25°C for batteries stored for one year or less.

Web: <https://wholesalesolar.co.za>